

FORM PTO-1390 (REV. 9-2001)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER Mo-6753/LeA 33,677	
TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371				U.S. APPLICATION NO. (If known, see 37 CFR 1.5) <div style="font-size: 1.5em; font-weight: bold;">09/980882</div> To Be Assigned	
INTERNATIONAL APPLICATION NO. PCT/EP00/03618		INTERNATIONAL FILING DATE 20 April 2000 (20.04.00)		PRIORITY DATE CLAIMED 06 May 1999 (6.05.99)	
TITLE OF INVENTION DIENE RUBBERS CONTAINING CARBOXYL GROUPS					
APPLICANT(S) FOR DO/EO/US					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
<ol style="list-style-type: none"> 1. <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. 4. <input checked="" type="checkbox"/> The US has been elected by the expiration of 19 months from the priority date (Article 31). 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). <ol style="list-style-type: none"> a. <input checked="" type="checkbox"/> is attached hereto. b. <input type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) <ol style="list-style-type: none"> a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). 					
Items 11 to 20 below concern document(s) or information included:					
<ol style="list-style-type: none"> 11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input checked="" type="checkbox"/> A FIRST preliminary amendment. 14. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 15. <input type="checkbox"/> A substitute specification. 16. <input type="checkbox"/> A change of power of attorney and/or address letter. 17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825. 18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 20. <input checked="" type="checkbox"/> Other items or information: 					
Form PTO 1449 w/references					

To Be Assigned

PCT/EP00/03618

ATTORNEY'S DOCKET NUMBER

Mo-6753/LeA 33,677

21. ☒ The following fees are submitted:**BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):**

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO. \$1040.00

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO \$890.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO
but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$740.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$710.00

International preliminary examination fee (37 CFR 1.482) paid to USPTO
and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00

ENTER APPROPRIATE BASIC FEE AMOUNT =**CALCULATIONS PTO USE ONLY**

\$ 890.00

\$ 0.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(e)).

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	
Total claims	5 - 20 =	0	x \$18.00	\$ 0.00
Independent claims	4 - 3 =	1	x \$84.00	\$ 84.00
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$280.00 \$ 0.00
TOTAL OF ABOVE CALCULATIONS =				\$ 974.00
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.				+ \$ 0.00
SUBTOTAL =				\$ 974.00
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$ 0.00
TOTAL NATIONAL FEE =				\$ 974.00
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$ 40.00
TOTAL FEES ENCLOSED =				\$ 1,014.00
				Amount to be refunded: \$
				charged: \$

a. ☐ A check in the amount of \$ _____ to cover the above fees is enclosed.

b. ☒ Please charge my Deposit Account No. 13-3848 in the amount of \$ 1,014.00 to cover the above fees.
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 13-3848. A duplicate copy of this sheet is enclosed.

d. ☐ Fees are to be charged to a credit card. **WARNING:** Information on this form may become public. **Credit card information should not be included on this form.** Provide credit card information and authorization on PTO-2038.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO.

SIGNATURE

Noland J. Cheung

NAME

39,138

REGISTRATION NUMBER

09/980882

JC10 Rec'd PCT/PTC 0 2 NOV 2001

PATENT APPLICATION
Mo6753
LeA 33,677

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

IN APPLICATION OF)
THOMAS SCHOLL ET AL) PCT/EP 00/03618
SERIAL NO.: TO BE ASSIGNED)
FILED: HEREWITH)
TITLE: DIENE RUBBERS CONTAINING)
CARBOXYL GROUPS)

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Upon the granting of a Serial Number and Filing Date and prior to the examination of the subject application, kindly amend the Specification and Claims as follows:

"Express Mail" mailing label number ET700176899US
Date of Deposit November 2, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231

Donna J. Veatch

(Name of person mailing paper or fee)


Signature of person mailing paper or fee)

IN THE SPECIFICATION:

Kindly replace the Title of the Invention with the following:

-- DIENE RUBBERS CONTAINING CARBOXYL GROUPS --.

IN THE ABSTRACT

Please replace page 16, a page containing an abstract with the enclosed page that contains a revised Abstract of the Disclosure. A separate page is enclosed herewith.

--DIENE RUBBERS CONTAINING CARBOXYL GROUPS

ABSTRACT OF THE DISCLOSURE

The present invention relates to rubber mixtures containing diene rubber with a concentration of carboxyl groups of 0.1 to 2 wt.% and a glass transition temperature of -120 to -50°C and their mixtures with fillers, optionally further rubbers and rubber auxiliary substances and vulcanisates prepared therefrom. Rubber mixtures according to the invention are suitable for producing highly reinforced, abrasion-resistant moulded items, in particular for producing tire treads which have a particularly high resistance to wet skidding, a high abrasion resistance and a low rolling resistance and also for tire sidewalls with especially good fatigue resistance.--

On page 1, line 3, kindly insert the following:

-- FIELD OF THE INVENTION --.

On page 1, line 12, kindly insert the following:

--BACKGROUND OF THE INVENTION--.

On page 2, line 11, kindly insert the following:

-- SUMMARY OF THE INVENTION --.

On page 11, line 1, kindly insert the following:

--Table 1--.

On page 11, kindly replace Table 1 with the following new Table 1.

--Table 1

	Comparison	Example
	2.A	2.1
in the kneader mixed:		
Buna VSL 5025-1 (37.5 phr mineral oil extended L-SBR, Bayer AG)	61.9	61.9
natural rubber	10	10
polybutadiene rubber Buna CB 45 (Bayer)	45	0
carboxylic group containing BR according example 1 (20 phr oil content)	0	54
mineral oil Enerthene 1849-1 (BP)	20	11
silica Vulkasil S (Bayer AG)	70	70
silane Si (69 (Degussa Hüls)	6	6
carbon black Corax N121 (Degussa Hüls)	10	10
zinc oxide	3	3
stearic acid	1	1
protective wax Antilux 654 (Rheinchemie)	1.5	1.5
antioxidant Vulkanox HS (Bayer AG)	1	1
antioxidant Vulkanox 4020 (Bayer AG)	1	1
On the mill admixed		
N-cyclohexylmercaptobenzthiazolsulfenamide		
Vulkacit CZ (Bayer AG)	1.8	1.8
diphenylguanidine Vulkacit D (Bayer AG)	2	2
sulfur	1.5	1.5

--

On page 12, line 1, kindly insert the following:

-- Table 2 --.

On page 12, kindly replace Table 2 with the following new Table 2.

[illegible]

►►

IN THE CLAIMS:

Kindly cancel Claims 1 - 5.

Kindly add the following new Claims:

- 6. A rubber mixture comprising one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.
7. A rubber mixture according to Claim 1, wherein said rubber is formed from diolefins.
8. A process for preparing a rubber with 0.1 to 2 wt.% of bonded carboxyl group comprising the step, after polymerization in solution, of reacting rubber with carboxylmercaptans of the general formula (I)



in which

R¹ represents a linear, branched or cyclic C₁-C₃₆ alkylene group, which may optionally be substituted with up to 3 further carboxyl groups, or which may be interrupted by nitrogen, oxygen or sulfur atoms, or a C₆-C₁₂-arylene group

and

X represents hydrogen or a metal or ammonium ion,

optionally in the presence of radical starters.

9. Molded items comprising rubber mixtures which comprise one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.
10. Tires comprising rubber mixtures which comprise one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber. --.

0990822 10201

REMARKS

The Applicants respectfully request the Preliminary Amendment be entered as the amendment places the claims as well as the Specification in proper form.

New Claims 6 - 10 replace now cancelled Claims 1 - 5. New Claims 10 and 11 replaces the use claim of now cancelled Claim 5. The Applicants respectfully submit that no new matter is added.

Respectfully submitted,

By



Noland J. Cheung
Attorney for Applicants
Reg. No. 39,138

Bayer Corporation
100 Bayer Road
Pittsburgh, Pennsylvania 15205-9741
PHONE: (412) 777-8338
FACSIMILE PHONE NUMBER:
412-777-8363

s/rmc/njc0105

10201 220860

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE SPECIFICATION: (Marked-Up)

The following are changes and additions made to the specification.

Kindly replace the Title Of The Invention with the following:

[CARBOXYL GROUP-CONTAINING] DIENE RUBBERS CONTAINING CARBOXYL GROUPS.

IN THE ABSTRACT

Please replace page 16, a page containing an abstract with the enclosed page that contains a revised Abstract of the Disclosure. A separate page is enclosed herewith.

--DIENE RUBBERS CONTAINING CARBOXYL GROUPS--

ABSTRACT OF THE DISCLOSURE

The present invention relates to rubber mixtures containing diene rubber with a concentration of carboxyl groups of 0.1 to 2 wt.% and a glass transition temperature of -120 to -50°C and their mixtures with fillers, optionally further rubbers and rubber auxiliary substances and vulcanisates prepared therefrom. Rubber mixtures according to the invention are suitable for producing highly reinforced, abrasion-resistant moulded items, in particular for producing tire treads which have a particularly high resistance to wet skidding, a high abrasion resistance and a low rolling resistance and also for tire sidewalls with especially good fatigue resistance.--

On page 1, line 3, kindly insert the following:

FIELD OF THE INVENTION

On page 1, line 12, kindly insert the following:

BACKGROUND OF THE INVENTION

On page 2, line 11, kindly insert the following:

SUMMARY OF THE INVENTION

On page 11, line 1, kindly insert the following:

--Table 1--

On page 11, kindly replace Table 1 with the following new Table 1.

	Comparison	Example
	2.A	2.1
in the kneader mixed:		
Buna VSL 5025-1 (37.5 phr mineral oil extended L-SBR, Bayer AG)	61[.].9	61[.].9
natural rubber	10	10
polybutadiene rubber Buna CB 45 (Bayer)	45	0
carboxylic group containing BR according example 1 (20 phr oil content)	0	54
mineral oil Enerthene 1849-1 (BP)	20	11
silica Vulkasil S (Bayer AG)	70	70
silane Si (69 (Degussa Hüls)	6	6
carbon black Corax N121 (Degussa Hüls)	10	10
zinc oxide	3	3
stearic acid	1	1
protective wax Antilux 654 (Rheinchemie)	1[.].5	1[.].5
antioxidant Vulkanox HS (Bayer AG)	1	1
antioxidant Vulkanox 4020 (Bayer AG)	1	1

On the mill admixed

N-cyclohexylmercaptobenzthiazolsulfenamide

Vulkacit CZ (Bayer AG)	1[.].8	1[.].8
diphenylguanidine Vulkacit D (Bayer AG)	2	2
sulfur	1[.].5	1[.].5

On page 12, line 1, kindly insert the following:

--Table--

IN THE CLAIMS:

Kindly cancel Claims 1 - 5.

Kindly add the following new Claims:

- 6. A rubber mixture comprising one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.
7. A rubber mixture according to Claim 1, wherein said rubber is formed from diolefins.
8. A process for preparing a rubber with 0.1 to 2 wt.% of bonded carboxyl group comprising the step, after polymerization in solution, of reacting rubber with carboxylmercaptans of the general formula (I)



in which

R^1 represents a linear, branched or cyclic $\text{C}_1\text{-C}_{36}$ alkylene group, which may optionally be substituted with up to 3 further carboxyl groups, or which may be interrupted by nitrogen, oxygen or sulfur atoms, or a $\text{C}_6\text{-C}_{12}$ -arylene group

and

X represents hydrogen or a metal or ammonium ion,

optionally in the presence of radical starters.

9. Molded items comprising rubber mixtures which comprise one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.
10. Tires comprising rubber mixtures which comprise one or more rubbers with 0.1 to 2 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.--

DIENE RUBBERS CONTAINING CARBOXYL GROUPSABSTRACT OF THE DISCLOSURE

The present invention relates to rubber mixtures containing diene rubber with a concentration of carboxyl groups of 0.1 to 2 wt.% and a glass transition temperature of -120 to -50°C and their mixtures with fillers, optionally further rubbers and rubber auxiliary substances and vulcanisates prepared therefrom. Rubber mixtures according to the invention are suitable for producing highly reinforced, abrasion-resistant moulded items, in particular for producing tire treads which have a particularly high resistance to wet skidding, a high abrasion resistance and a low rolling resistance and also for tire sidewalls with especially good fatigue resistance.

0993022 10201

09/980882

- 1 -

JC10 Rec'd PCT/PTO 02 NOV 2001

Carboxyl group-containing diene rubbers

5 The present invention provides rubber mixtures which contain a diene rubber with a concentration of carboxyl groups of 0.1 to 2 wt.% and a glass transition temperature of -120 to -50° and their mixtures with fillers, optionally other rubbers and rubber auxiliary substances and vulcanisates prepared therefrom. Rubber mixtures according to the invention are suitable for producing highly reinforced, abrasion-resistant moulded items, in particular for producing tire treads which have particularly high wet skidding resistance and abrasion resistance and a low rolling resistance and also for tire sidewalls with especially high fatigue resistance.

10 Double bond-containing anionic polymerised solution rubbers, such as solution polybutadiene and solution styrene/butadiene rubbers, have advantages over the corresponding emulsion rubbers when producing low rolling resistance tire treads. The advantages are based, inter alia, on the ability to control the vinyl content and the glass transition temperature and molecular branching associated therewith. Particular advantages in relation to the wet skidding resistance and rolling resistance of the tires result therefrom in a practical application. Thus, US-A 5 227 425 describes the production of tire treads from a solution SBR rubber and silica. To further improve the properties, numerous methods for modifying the end groups have been developed, as is described in EP-A 334 042, with dimethylaminopropyl-acrylamide or, as described in EP-A 447 066, with silyl ethers. However, due to the high molecular weight of the rubber, the proportion by weight of the end group is small and can therefore have only a small effect on the interaction between filler and rubber molecule. Inter alia, the present invention is intended to provide diene rubbers with a much higher concentration of effective groups for interacting with fillers and with a particularly low glass transition temperature.

US-A 2 662 874 describes the preparation of elastic materials from metal ion cross-linked polymeric carboxylates with a concentration of 0.001 to 0.3 carboxyl equiva-

"Express Mail" mailing label number FT7017622915
Date of Deposit November 2, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner of Patents and Trademarks, Washington, D.C. 20231

Donna I. Veatch
(Name of person mailing paper or fee)

Signature of person mailing paper or fee

lents per 100 g of rubber. The elastic materials mentioned have a very wide range of carboxyl group contents and are unsuitable for the tire application in the present invention due to the inherent sensitivity to hydrolysis of the metal salts.

5 A process for preparing carboxyl group-containing (3.9 to 8.9 wt.% of carboxyl groups) solution polybutadiene rubbers is described, inter alia, in DE-OS 2 653 144. These rubbers have glass transition temperatures which are too high ($> -50^{\circ}\text{C}$) due to the high concentration of vinyl and carboxyl groups and are associated with disadvantageous damping properties and are therefore not a substitute for 1,4-polybutadiene rubber in tire treads and tire sidewalls.

10 Therefore the present invention was intended to provide mixtures of carboxyl group-containing solution rubbers from which tires with improved wet skidding resistance, lower rolling resistance and high mechanical strength and improved abrasion behaviour can be produced.

15 The present invention therefore provides rubber mixtures containing one or more rubbers with a concentration of bonded carboxyl groups or their salts in the range 0.1 to 2 wt.% and with a glass transition temperature in the range -120 to -50°C and one or more fillers in the range 10 to 500 parts by wt. with respect to 100 parts by wt. of rubber.

20 Preferred rubber mixtures according to the invention are those in which the carboxyl group-containing rubber has a concentration of bonded carboxyl groups or their salts of 0.1 to 1 wt.% and a glass transition temperature in the range -120 to -50°C , preferably -120 to -70°C and a concentration of 1,2-bonded diolefins (vinyl content) in the range 0 to 50 wt.%, in particular 1 to 15 wt.% and a cis-1,4-content in the range 30 to 100 wt.%, in particular preferably 90 to 100 wt.% and also has an average molecular weight (number average) of 50 000 to 2 000 000, preferably 100 000 to 1 000 000 and Mooney viscosities ML 1+4 (100°C) of 10 to 200, preferably 30 to 150.

5

10

20

25

30



in which

- 5 R^1 represents a linear, branched or cyclic $\text{C}_1\text{-C}_{36}$ alkylene group, which may optionally be substituted with up to 3 further carboxyl groups, or which may be interrupted by nitrogen, oxygen or sulfur atoms or a $\text{C}_6\text{-C}_{12}$ -arylene group,

and

10

- X represents hydrogen or a metal or ammonium ion.

This process is a further subject of the invention.

15

$\text{C}_1\text{-C}_{36}$ alkylene groups are understood to be any linear, cyclic or branched alkylene groups with 1 to 36 carbon atoms which are known to a person skilled in the art, such as methylene, ethylene, n-propylene, i-propylene, n-butylene, i-butylene, t-butylene, n-pentylene, i-pentylene, neo-pentylene, n-hexylene, cyclohexylene, i-hexylene, heptylene, octylene, nonylene, decylene, undecylene and dodecylene.

20

Preferred carboxylmercaptans of the formula (I) are thioglycollic acid, 2-mercaptopropionic acid (thiolactic acid), 3-mercaptopropionic acid, 4-mercaptobutyric acid, mercaptoundecanoic acid, mercaptooctadecanoic acid, 2-mercaptosuccinic acid and their alkali and alkaline earth metal or ammonium salts.

25

3-mercaptopropionic acid, mercaptobutyric acid, 2-mercaptosuccinic acid 2- and 4-mercaptobenzoic acid and their lithium, sodium, potassium, magnesium, calcium or ammonium salts are particularly preferred. 3-mercaptopropionic acid and its lithium, sodium, potassium, magnesium, calcium or ammonium salts are more particularly preferred.

30

In general, reaction of the carboxylmercaptans with the solution rubbers is performed in a solvent, for example hydrocarbons such as pentane, hexane, cyclohexane, benzene and/or toluene, at temperatures of 40 to 150°C in the presence of radical starters, e.g. peroxides such as dilauroyl peroxide, azo-initiators such as azobisisobutyronitrile, benzopinacolsilyl ethers or in the presence of photo-initiators and visible or UV light. Preferred radical starters are diacyl peroxides such as dilauroyl peroxide, didodecanoyl peroxide, di-(3,5,5-trimethylhexanoyl) peroxide and perketals such as 1,1-di-(tert.-butylperoxy)-3,3,5-trimethylcyclohexane, 1,1-di-(tert.-butylperoxy)-cyclohexane and 1,1-di-(tert.-butylperoxy)-butane.

The amount of carboxylmercaptans to be used is governed by the concentration of bonded carboxyl groups or their salts required in the solution rubber being used in the rubber mixtures.

The carboxylate salts may also be prepared after introduction of the carboxylic acids groups into the rubber, by neutralising them.

Suitable fillers for rubber mixtures according to the invention are any fillers which are known to be used in the rubber industry, these including both active and inactive fillers.

The following may be mentioned:

- highly disperse silicas prepared e.g. by precipitation from solutions of silicates or by flame hydrolysis of silicon halides with specific surface areas of 5 - 1000, preferably 20 - 400, m²/g (BET surface area) and with primary particle sizes of 10 - 400 nm. The silicas may also optionally be present as mixed oxides with other metal oxides such as Al, Mg, Ca, Ba, Zn, Zr or Ti oxides;

- synthetic silicates such as aluminium silicate or alkaline earth metal silicates such as magnesium silicate or calcium silicate, with BET surface areas of 20 - 400 m²/g and primary particle diameters of 10 - 400 nm;
- 5 - natural silicates such as kaolin and other naturally occurring silicas;
- glass fibre and glass fibre products (mats, ropes) or glass microbeads;
- metal oxides such as zinc oxide, calcium oxide, magnesium oxide, aluminium oxide;
- metal carbonates such as magnesium carbonate, calcium carbonate, zinc carbonate;
- 10 - metal hydroxides such as e.g. aluminium hydroxide, magnesium hydroxide;
- carbon blacks. The carbon blacks to be used here are prepared by the lamp black, furnace black or channel black processes and have BET surface areas of 20 - 200 m²/g, e.g. SAF, ISAF, HAF, FEF or GPF carbon blacks;
- 15 - rubber gels, in particular those based on polybutadiene, butadiene/styrene copolymers, butadiene/acrylonitrile copolymers and polychloroprene.

20 Highly disperse silicas and/or carbon blacks are preferably used as fillers.

The fillers mentioned may be used individually or as a mixture. In a particularly preferred embodiment, the rubber mixtures contain a mixture of pale-coloured fillers, such as highly disperse silicas, and carbon blacks, as filler, wherein the mixing ratio of pale-coloured fillers to carbon blacks is 0.05 to 20, preferably 0.1 to 10.

25

The fillers are then used in amounts in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber. 20 to 200 parts by wt. are preferably used.

Rubber mixtures according to the invention may contain, in addition to one, two, three or more different carboxyl group-containing solution rubbers according to the invention, other rubbers such as natural rubber or also other synthetic rubbers.

- 5 Preferred synthetic rubbers are described, for example, in W. Hoffmann, Kautschuk-technologie, Gentner Verlag, Stuttgart 1980 and I. Franta, Elastomers and Rubber Compounding Materials, Elsevier, Amsterdam, 1989. They include, inter alia,

	BR	polybutadiene
10	ABR	butadiene/C ₁ -C ₄ -alkyl acrylate copolymers
	CR	polychloroprene
	IR	polyisoprene
	SBR	styrene/butadiene copolymers with styrene contents of 1-60, preferably 20-50 wt. %
15	IIR	isobutylene/isoprene copolymers
	NBR	butadiene/acrylonitrile copolymers with acrylonitrile contents of 5-60, preferably 10-40 wt. %
	HNBR	partially hydrogenated or fully hydrogenated NBR rubber
	EPDM	ethylene/propylene/diene copolymers

20

and mixtures of these rubbers. For producing vehicle tires, natural rubber, emulsion SBR and solution SBR rubbers with a glass transition temperature above -50°C, which may optionally be modified with silyl ethers or other functional groups, e.g. according to EP-A 447 066, polybutadiene rubber with a high 1,4-cis content (>90
25 %), which has been prepared using catalysts based on Ni, Co, Ti or Nd, and polybutadiene rubber with a vinyl content of up to 75 % and their mixtures are of particular interest.

30

Rubber mixtures which are quite specifically preferred according to the invention contain, in addition to one or more carboxyl group-containing rubbers with a glass transition temperature between -110° and -50°C, additional rubbers chosen from the

group consisting of natural rubber, polyisoprene and styrene/butadiene copolymers with styrene contents between 10 and 50 wt.%. The amount of these additional rubbers is usually in the range 0.5 to 95, preferably 40 - 90 wt.%, with respect to the entire amount of rubber in the rubber mixture. The amount of these additionally added rubbers is again governed by the particular intended use of the rubber mixtures according to the invention.

Obviously, rubber mixtures according to the invention may also contain other rubber auxiliary substances which are used, for example, to cross-link the vulcanisates produced from the rubber mixtures or which improve the physical properties of the vulcanisates produced from rubber mixtures according to the invention for a specific ultimate use.

Sulfur or sulfur-providing compounds, and also radical-providing cross-linking agents such as organic peroxides may be used, for example, as cross-linking agents. Sulfur is preferably used as a cross-linking agent. In addition, as mentioned above, rubber mixtures according to the invention may contain further auxiliary substances such as known reaction accelerators, antioxidants, thermal stabilisers, light stabilisers, anti-ozonants, processing aids, plasticisers, tackifiers, blowing agents, colorants, pigments, waxes, extenders, organic acids, delaying agents, metal oxides and activators.

The rubber auxiliary substances according to the invention are used in conventionally disclosed amounts, wherein the amount used is governed by the later ultimate use of the rubber mixtures. Amounts of rubber auxiliary substances in the range 2 to 70 parts by wt., with respect to 100 parts by wt. of rubber, are, for example, conventionally used.

In the case of rubber mixtures according to the invention which are filled with highly active silicas, the use of additional filler activators is particularly advantageous. Preferred filler activators are sulfur-containing silyl ethers, in particular bis-(tri-

alkyloxysilyl-alkyl)-polysulfides, as are described in DE 2 141 159 and DE 2 255 577. In addition, oligomers and/or polymers of sulfur-containing silyl ethers corresponding to the description in DE 4 435 311 and EP 670 347 are also suitable. Mercaptoalkyltrialkoxysilanes, in particular mercaptopropyltriethoxysilane and thio-
5 cyanatoalkyl silyl ethers (see DE 19 544 469) may also be used. The filler activators are used in conventional amounts, i.e. in amounts of 0.1 to 15 parts by wt., with respect to 100 parts by wt. of rubber.

Rubber mixtures according to the invention may be prepared, for example, by mixing
10 the carboxyl group-containing solution rubber with the corresponding fillers and optionally further rubbers and further rubber auxiliary substances in appropriate mixing equipment such as compounders, rollers or extruders.

Rubber mixtures according to the invention are preferably prepared by first polymerising the monomers mentioned in solution, introducing the carboxyl groups into
15 the solution rubber and, after completing polymerisation and introduction of the carboxyl groups, mixing the solution rubber in the corresponding solvent with the appropriate fillers and optionally further rubbers and further rubber auxiliary substances, in particular plasticisers, in appropriate amounts, and then removing the solvent with hot water and/or steam at temperatures of 50 to 200°C, preferably under
20 vacuum.

The invention also provides use of the rubber mixtures according to the invention for producing moulded items of all types, in particular for producing tires, especially tire
25 treads and tire sidewalls.

Examples

Example 1

- 5 6.25 of 3-mercaptopropionic acid and 1 g of dilauroylperoxide were added to a solution of 500 g solution polybutadiene rubber, CB 45 NF (Bayer AG, Li-type, cis-1,4-content about 40%) in 4 l cyclohexane at 80°C. The mixture was then stirred for 7 hours at 80°C. Then 2,5 antioxidant Vulkanox 4020 (Bayer AG) and 101.3 g aromatic mineral oil Enerthene 1849-1 (BP) were added and the solvent was distilled off
- 10 using steam (100-110°C). After drying at 70°C under vacuum, 593 g of rubber extended with 20 phr mineral oil were obtained. Sulfur content 0.3 wt%, carboxyl group content 0.5 wt% (based on rubber), viscosity ML 1+4 (100°C) 59, cis-1,4-content 40%, glass transition temperature: -88°C.

15 Example 2:

The following rubber mixtures were prepared in a 1.5 l kneader (mixing time 5 minutes, ejection temperature 150°C). Sulfur and accelerator were admixed afterwards on a mill (50°C):

Comparison 2.A Example 2.1

in the kneader mixed:

Buna VSL 5025-1 (37,5 phr mineral oil extended L-SBR, Bayer AG)

	61,9	61,9
natural rubber	10	10
polybutadiene rubber Buna CB 45 (Bayer)	45	0
carboxylic group containing BR according example 1 (20 phr oil content)	0	54
mineral oil Enerthene 1849-1 (BP)	20	11
silica Vulkasil S (Bayer AG)	70	70
silane Si (69 (Degussa Hüls)	6	6
carbon black Corax N121 (Degussa Hüls)	10	10
zinc oxide	3	3
stearic acid	1	1
protective wax Antilux 654 (Rheinchemie	1,5	1,5
antioxidant Vulkanox HS (Bayer AG)	1	1
antioxidant Vulkanox 4020 (Bayer AG)	1	1

On the mill admixed

N-cyclohexylmercaptobenzthiazolsulfenamide

Vulkacit CZ (Bayer AG)	1,8	1,8
diphenylguanidine Vulkacit D (Bayer AG)	2	2
sulfur	1,5	1,5

The rubber mixtures were subsequently vulcanized at 170°C for 15 minutes. The following vulcanisate properties were obtained.

	Comparison 2.A	Example 2.1
tensile strength (Mpa)	16,8	18,2
elongation at break (%)	450	330
modulus at 100%	2,4	2,9
modulus at 300% elongation (Mpa)	9,5	16,3
rebound elasticity at 70°C (%)	54	63
hardness (shore A)	66	66
tan delta at 70°C	0,138	0,108

The experimental data confirm the significant lower dynamic damping at 70°C, measured by rebound elasticity and tan delta, which in practice correlates with a significantly reduced rolling resistance in tires.

5

Example 3:

Preparing a masterbatch from precipitated silica and carboxyl group-containing BR rubber:

10

Using the method in example 1, 500 g of BR rubber Buna CB 65 in 4 l of cyclohexane at 80°C were reacted with 12.5 g of 3-mercaptopropionic acid and 0,5 g of dilauryl peroxide. Reaction time: 5 hours. At this point 36% of the 3-mercaptopropionic acid had reacted. The carboxyl group content of the polymer was 0.38 wt.%. Then, with stirring at 75°C, 2.5 g of stabiliser Vulkanox® 4020 (Bayer AG), 189.5 g of aromatic mineral oil Renopal® 450 (Fuchs Mineralölwerke) and 405 g of highly active precipitated silica Vulkasil® S (N₂ surface area about 180 m²/g, Bayer AG) were added and the mixture was stirred for about 30 minutes at this temperature until these components were uniformly distributed. The solvent was then removed by passing steam (100-110°C) through the mixture. The reaction vessel was heated to 75-80°C from outside during this procedure. Finally, the moist solid was removed, finely divided silica was filtered off through a sieve, and the product was dried at 65°C under

15

20

vacuum. 1090 g of a brown silica/rubber masterbatch (99 % of theoretical) were obtained. The waste water contained no silica.

Comparison example 3.A:

5

The same procedure was used as described in example 3, wherein a solution of 500 g of BR rubber Buna CB 65 and 2.5 g of Vulkanox[®] 4020 in 4 l of cyclohexane were mixed at 75°C with 400 g of highly active silica Vulkasil[®] S. The solvent was then removed by passing steam (100-110°C) through the mixture, wherein the reaction

10 vessel was heated to 75-80°C from outside. Finally, the moist solid was removed, finely divided silica was filtered off through a sieve and the product was then dried at 65°C under vacuum. 597 g (66 % of theoretical) of an inhomogeneous silica/rubber masterbatch were obtained. The waste water contained large amounts (about 75 % of the amount used) of silica.

15

09980882 110201

Claims

1. A rubber mixture containing one or more rubbers with in the range of 0.1 to 2
5 wt.% of bonded carboxyl groups or their salts and a glass transition temperature in the range from -120° to -50°C and one or more fillers in the range 10 to 500 parts by wt., with respect to 100 parts by wt. of rubber.
2. A rubber mixture according to Claim 1, characterised in that the rubber is
10 built up from diolefins.
3. A process for preparing a rubber with in the range of 0.1 to 2 wt.% of bonded
carboxyl groups, characterised in that, after polymerisation in solution, the
15 rubber is reacted with carboxylmercaptans of the general formula (I)



in which

- 20 R^1 represents a linear, branched or cyclic $\text{C}_1\text{-C}_{36}$ alkylene group, which may optionally be substituted with up to 3 further carboxyl groups, or which may be interrupted by nitrogen, oxygen or sulfur atoms, or a $\text{C}_6\text{-C}_{12}$ -arylene group

25 and

X represents hydrogen or a metal or ammonium ion,

optionally in the presence of radical starters.

30

4. Use of rubber mixtures according to Claim 1 to prepare moulded items of all types.
5. Use of rubber mixtures according to Claim 1 to produce tires.

5

0990882 110201

ATTORNEY DOCKET NO

DIENE RUBBERS CONTAINING CARBOXYL GROUPS

as a PCT Application Serial No. **PCT/EP00/03618**

Prior Foreign Application(s), the priority(ies) of which is/are to be claimed:

May 6, 1999
(Month/Day/Year Filed)

I hereby claim the benefit under Title 35, United States Code, §120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose the material information as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing Date)	(Status)
		(patented, pending, abandoned)

Le A 33 677-US

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and this application and to transact all business in the Patent and Trademark Office

JOSEPH C. GIL, Patent Office Registration Number 26,602 ARON PREIS, Patent Office Registration Number 29,426
LYNDANNE M. WHALEN, Patent Office Registration Number 29,457 THOMAS W. ROY,
Patent Office Registration Number 29,582 RICHARD E. L. HENDERSON, Patent Office Registration Number 31,619
GODFRIED R. AKORLI, Patent Office Registration Number 28,779 N. DENISE BROWN, Patent Office
Registration Number 36,097 NOLAND J. CHEUNG, Patent Office Registration Number 39,138
DIDERICO VAN EYL, Patent Office Registration Number 38,641 CAROLYN M. SLOANE, Patent Office
Registration Number 44,339 JAMES R. FRANKS, Patent Office Registration Number 42,552
JACKIE ANN ZURCHER, Patent Office Registration Number 42,251
RAYMOND J. HARMUTH, Patent Office Registration Number 33,896

all of Bayer Corporation, Pittsburgh, Pennsylvania 15205-9741

Send Correspondence To: Direct Telephone Calls To:

Patent Department

Bayer Corporation (412) 777-2349

100 Bayer Road

Pittsburgh, Pennsylvania 15205-9741

FULL NAME OF SOLE OR FIRST INVENTOR Thomas Scholl (deceased)		INVENTOR'S SIGNATURE	DATE
RESIDENCE D 51469 Bergisch Gladbach, Germany DE		CITIZENSHIP German	
POST OFFICE ADDRESS Alte Wipperfurth Str. 24A, D 51469 Bergisch Gladbach, Germany			
FULL NAME OF THE HEIRS Ulrike, Philipp, Christine, Johannes Scholl		HEIR'S SIGNATURE Ulrike Scholl	DATE 2001-10-13
RESIDENCE D 51469 Bergisch Gladbach, Germany DE		CITIZENSHIP German	
POST OFFICE ADDRESS Alte Wipperfurth Str. 24A, D 51469 Bergisch Gladbach, Germany			
FULL NAME OF SECOND INVENTOR Jürgen Trimbach		INVENTOR'S SIGNATURE Jürgen Trimbach	DATE 2001-10-11
RESIDENCE D 50859 Köln, Germany DE		CITIZENSHIP German	
POST OFFICE ADDRESS c/o BAYER AKTIENGESELLSCHAFT, D 51368 Leverkusen, Germany			
FULL NAME OF THIRD INVENTOR		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
FULL NAME OF FOURTH INVENTOR		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
FULL NAME OF FIFTH INVENTOR		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			
FULL NAME OF SIXTH INVENTOR		INVENTOR'S SIGNATURE	DATE
RESIDENCE		CITIZENSHIP	
POST OFFICE ADDRESS			